



118db Siren alarm

Specifications

Model: FBXS02

Siren alarm (receiver):

Mounted on the top of door of hospital wards / office / patient rooms / guest house rooms / hotel suites etc.

Loud 118db siren sound when panic button is pressed

Wall mount calling unit:

Size: 150 x 90 x 55 mm

Weight: 450 gms

Features:

- 118db loud siren
- 1 indicator RED light in the front
- 1 indicator BLUE SYNC light to check signal reception
- Starts siren on press of panic alarm button
- Stops the indicator on release of panic alarm button

Operating voltage: (12V)

110-220VAC/50-60Hz to 12VDC converter adapter supplied.

Unit can also be plugged to any 12V external battery. Active working hours depends on the battery power

RF configurations:

Operating frequency: 380 – 480 MHz

System works on signal hop mechanism. Reception happens at more than 12-15 predefined frequencies

Modulation type: GFSK

Radio IC: CC1100 (Chipcon/TI) and equivalents in sub-GHz freq.

Receiver sensitivity: – 112 dbm

Application and features:

- Alerts building security or maintenance staff in case of emergency from anywhere inside the building

FORBIX SEMICON Co.

Bangalore, India

Website: www.forbixindia.com

Website: www.forbixsemicon.com

Email: sales@forbixindia.com

+91 9742370190(M) / +91 9742159846(M)

+91 80 6452 1122(L)

FORBIX SEMICON

