



Wireless peon calling systems(FBWACS03)

FORBIX SEMICON Co.
Bangalore, India

Website: www.forbixindia.com

Website: www.forbixsemicon.com

Email: sales@forbixindia.com

+91 9742370190(M) / +91 9742159846(M)

+91 80 6452 1122(L)

Specifications

Model: FBWACS03

Range of communication:

20 – 30 meters indoors

100 – 120 meters outdoors (line of sight)

Wireless peon calling system:

Receiver indicator Size: 160 x 100 x 35 mm

Weight: 230 gms

Remote controller size: 120 x 40 x 20 mm

Remote controller weight: 45 gms

Features:

3 BLUE indicator – one for each corresponding remote (01 to 03)

1 green light indicator for power supply (on indicator receiver)

1 buzzer, blows when call button pressed

Remote has 1 red light indicator to indicate button press

Remote TOP button: to call (summon) peon

Remote BOTTOM button: to cancel the call

Operating voltage: (12VDC)

110-220VAC/50-60Hz to 12VDC converter adapter supplied.

Receiver unit can also be plugged to any 12V external battery.

Battery operated (12VDC), battery type: 23A

Battery life 2-4 years (active working hours depends on the battery power)

Battery replicable: Yes

RF configurations:

Operating frequency: 380 – 480 MHz

System works on signal hop mechanism. Transmission happens at more than 12-15 predefined frequencies

Modulation type: GFSK

Radio IC: CC1100 (Chipcon/TI) and equivalents in sub-GHz freq.

PA: +10dbm

Signal transmissions:

Make sure to press the remote controller for not less than 2-3 seconds for successful signal transmission

Application and features:

- Office peon calling
- School / educational institution peon calling
- Staff summon system
- Restaurant waiter calling system

