



Range of communication:

- 20 – 30 meters indoors
- 100 – 120 meters outdoors (line of sight)

Precautions and mounting locations:

- Caller and receiver units can mounted on the top of door / wall / bed
- For indoor purpose use only
- Keep away from metallic enclosures
- Do not connect the battery in opposite direction

Wireless staff calling system:

Receiver indicator size: 160 x 100 x 35 mm

Weight: 230 gms

Calling unit size: 160 x 100 x 35 mm

Calling unit weight: 230 gms

Model: FBXWCCS04

Wireless staff calling system with ACKNOWLEDGEMENT

Features:

- Press GREEN button (on the calling unit) to call staff member
- Indicator receiver with the staff
- 1 buzzer blows on the receiver when called
- Acknowledgement indicator at the calling unit. This feature ensures that the call has landed to the receiver successfully

Technical details:

- Remote transmitter PA +10dbm
- Receiver sensitivity: – 110dbm
- Operating frequency: 380 – 480 MHz
- System operates works on signal hop mechanism. Signal transmission happens at more than 12-15 predefined frequencies
- Modulation type: GFSK
- Radio IC: CC1100 (Chipcon/TI) and other equivalents in sub-GHz freq.
- Modulation: GFSK
- Data packet error correction mechanism: FEC

Operating voltage:

12 Volt DC (110-220VAC/50-60Hz) adapter supplied

Signal transmissions:

Make sure to press a button for at least 2-3 seconds for reliable transmission. This increases the range of communication

Application and features:

- Nurse call system for hospitals: remote with patients
- Steam bath sauna rooms / spas / restaurants etc.
- OPD token system for dispensaries: remote with doctors
- Office peon calling system: remote with clerk / manager
- Guest house attendant call unit: remote with customers in room
- Office peon calling, school peon calling system

FORBIX SEMICON INDIA PVT. LTD.

Bangalore, India

Website: <https://www.forbixindia.com>

+91 9742370190 / +91 9742159846

FORBIX Osäuhing,

Tallinn, Estonia

Website: <https://www.forbix.eu>

+372 880 1510

Email: sales@forbixindia.com